

A Practical P-Delta Analysis Method for Type FR and PR Frames

Paper by ERIC M. LUI
(3rd Quarter 1988)

The following errors to the subject paper occurred and should be corrected.

Page 85:

Col. 1, para. 1, line 7: line should read “sis and design processes. There are various approaches”

Page 88:

Col. 2, para. 2, line 2: “cosider” should read “consider.”

Equation 11 should read:

$$M_{max} = \left[\frac{\tan\left(\frac{kL}{2}\right)}{\left(\frac{kL}{2}\right)} \right] M_o$$

Page 92:

Col. 1, para. 3, line 1: “preceeding” should read “preceding”

Page 93:

Table 3a: Fourth equation of Load Case 2 should read:

$$\alpha_4 = 2a^2 + 3ab + b^2$$

First equation of Load Case 3 should read:

$$\alpha_1 = \alpha_2 = 4$$

Equation (19a) should read:

$$M_{FA}^c = \frac{\left(1 + \frac{4EI}{LR_{kB}}\right) M_{FA} - \frac{2EI}{LR_{kB}} M_{FB}}{\left(1 + \frac{4EI}{LR_{kA}}\right) \left(1 + \frac{4EI}{LR_{kB}}\right) - \left(\frac{4}{R_{kA}R_{kB}}\right) \left(\frac{EI}{L}\right)^2}$$