

CORRECTIONS

Simple Equations for Effective Length Factors

Paper by PIERRE DUMONTEIL
(AISC Engineering Journal, Third Quarter, 1992)

p. III, Equation 4 should read:

$$K = \frac{3G_A + 1.4}{3G_A + 2.0}$$

p. 112, Table 2 should read:

Table 2. Comparison of Eqs. 7 and 8—Unbraced frames								
G_A	0.100	0.250	0.100	0.250	0.500	0.100	0.250	0.500
G_B	0.400	0.250	0.900	0.750	0.500	1.900	1.750	1.500
K exact	1.083	1.083	1.159	1.162	1.164	1.286	1.295	1.307
K approx.	1.090	1.100	1.170	1.180	1.180	1.290	1.310	1.330
Error, percent	1.000	1.200	1.000	1.400	1.700	0.300	0.800	1.400
G_A	1.000	0.500	1.000	2.500	0.500	1.000	2.500	5.000
G_B	1.000	4.500	4.000	2.500	9.500	9.000	7.500	5.000
K exact	1.317	1.575	1.634	1.711	1.777	1.874	2.092	2.228
K approx.	1.340	1.580	1.650	1.730	1.770	1.880	2.100	2.240
Error, percent	1.800	0.200	0.800	1.200	-0.200	0.400	0.600	0.400